

13-2027210 - LEDFLEX IN MP 927 5M

13-2030210 - LEDFLEX IN MP 930 5M

13-2040210 - LEDFLEX IN MP 940 5M




## 1. Specifications

- Number Led/M : 210pcs
- Input voltage (DC) : 24V
- Power W/m±10% : 10W
- Width for finished product : 10mm
- CRI : >90
- Max length(10% voltage drop) : 5m
- Cut Size : 33.3mm

## Standards / Normative Requirements

- Eye security : IEC 62471
- Protection class : EN 60529
- Safety Requirements : EN 62031 IEC 60598-1
- EMC / radio disturbance characteristics : EN 55015
- ROHS : Yes
- UL : Yes

## 2. Dimension



LEDsGO BVBA

Drieslaan 6 | B-8560 Wevelgem (Moorsele) | Tel +32 (0) 56 424 992 | Fax +32 (0) 56 435 707  
 BTW BE 0824.326.685 | ING IBAN BE47 3630 7083 3480 | BIC BBRUBEBB

### 3. Product Parameters:

| Part No    | CCT(K) | CRI | R9  | Pow(W/m) | LM/W | LM/M | VDC | IP |
|------------|--------|-----|-----|----------|------|------|-----|----|
| 13-2027210 | 2700   | >90 | >50 | 10       | 101  | 1010 | 24  | 20 |
| 13-2030210 | 3000   | >90 | >50 | 10       | 104  | 1040 | 24  | 20 |
| 13-2040210 | 4000   | >90 | >50 | 10       | 107  | 1070 | 24  | 20 |

### 4. Packing

10 Silicone mounting brackets per reel(5m) included in the package.

### 5. Precautions

1. The given data has typical values, Due to tolerances of the production process and electrical components, electrical power can be  $\pm 10\%$
2. Less than 14.4W/M(4.39W/feet)no need for additional heat sinking on Alu profile, if more than 14.4W/M(4.39W/feet) must be used the heat sinking.